

Filter Service Sp. z o.o.  
ul. Sadowa 7a  
95-100 Zgierz

Tel/Fax: (+48 42) 716 15 18  
Tel/Fax: (+48 42) 717 15 81  
Fax: (+48 42) 717 15 15  
Fax: (+48 42) 715 44 33  
Email: [filter@filter-service.eu](mailto:filter@filter-service.eu)  
[www.filter-service.eu](http://www.filter-service.eu)

Filtering half mask

## FILTROSTAT FS CODE 823V FFP2 NR D

Certificate

UE/982/2024/1437

Date of issue

08.04.2024

Standard

EN 149:2001 + A1:2009

Protection class

Class P2



Certification body:

CIOP-PIB 1437  
Central Institute for Labour  
Protection – National  
Research Institute

Supervising body:

CIOP-PIB 1437\*  
Central Institute for Labour  
Protection – National  
Research Institute



## Intended use

For protecting the user's respiratory tract against the harmful impact of air pollution in the form of solid and/or liquid particles forming aerosol (dust, fumes, mists) up to 10 × TLV.

## Application

Medium-toxic particulate matter, dusts of asbestos, copper, barium, titanium, vanadium, chromium, manganese, wood dusts, coal dust containing more than 10% of free silica, mining industry, chemical industry, metallurgical industry (the version with the exhalation valve).

## Specification

Half mask face-piece:

- Protective non-woven fabric
- Electret needled non-woven fabric
- Non-woven polypropylene melt blown fabric
- Protective non-woven fabric

Additional elements:

- Exhalation valve
- Nosepiece for better facial fit within the nose area
- Polyethylene foam nose seal
- Head band pins for length adjustment
- Head band

Compact, face-fitting shape, pleasant-to-touch and delicate material. The half mask is covered with a special protective nonwoven layer, which prolongs its life. With the valve placed at the side of the half mask, it can be folded and put into a pocket without damaging it.

Filter Service Sp. z o.o.  
 ul. Sadowa 7a  
 95-100 Zgierz

Tel/Fax: (+48 42) 716 15 18  
 Tel/Fax: (+48 42) 717 15 81  
 Fax: (+48 42) 717 15 15  
 Fax: (+48 42) 715 44 33  
 Email: [filter@filter-service.eu](mailto:filter@filter-service.eu)  
[www.filter-service.eu](http://www.filter-service.eu)

Filtering half mask

**FILTROSTAT FS CODE 823V FFP2 NR D**

Certificate UE/982/20124/1437	Date of issue 08.04.2024	Standard EN 149:2001 + A1:2009	Protection class Class P2 
----------------------------------	-----------------------------	-----------------------------------	--

Certification body:  
 CIOP-PIB 1437  
 Central Institute for Labour  
 Protection – National  
 Research Institute



Supervising body:  
 CIOP-PIB 1437\*  
 Central Institute for Labour  
 Protection – National  
 Research Institute

## Requirements

The half mask meets the latest requirements:

**Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment** and repealing Council Directive 89/686/EEC.

## Contraindications

The half mask must not be used under low-oxygen conditions (below 17%), which means that it is forbidden to use it in confined spaces, such as canals, manhole shafts, tanks. Also, the half mask does not protect against vapours and gases that are harmful for health and pose a life hazard. Do not use while extinguishing fire. The half mask does not supply oxygen. The half mask will not provide adequate facial fit for people with unshaved or bearded face. The half mask does not protect against aerosols containing radioactive and carcinogenic particles, microorganisms (bacteria, viruses, fungi and their derivatives) or enzymes.

Primary packaging: 15 pcs per box

Collective packaging: 360 pcs per carton

\*This number is on the product after the CE mark