

Filter Service Sp. z o.o.
ul. Sadowa 7a
95-100 Zgierz

Tel/Fax: (+48 42) 716 15 18
Tel/Fax: (+48 42) 717 15 81
Fax: (+48 42) 717 15 15
Fax: (+48 42) 715 44 33
Email: filter@filter-service.eu
www.filter-service.eu

Filtering half mask

FS-623V FFP2 NR D

Certificate

UE/1117/2025/1437
Edition 1

Date of issue

12.02.2025

Standard

EN 149:2001 + A1:2009

Protection class

Class P2



Certification body:

CIOP-PIB 1437
Central Institute for Labour
Protection – National
Research Institute

Supervising body:

CIOP-PIB 1437*
Central Institute for Labour
Protection – National
Research Institute



Intended use

For protecting the user's respiratory tract against the harmful impact of air pollution in the form of solid and/or liquid particles forming aerosol (dust, fumes, mists) up to 10 × TLV.

Application

Medium-toxic particulate matter, dusts of asbestos, copper, barium, titanium, vanadium, chromium, manganese, wood dusts, coal dust containing more than 10% of free silica, mining industry, chemical industry, metallurgical industry (the version with the exhalation valve).

Specification

Half mask face-piece:

- Polyester construction non-woven fabric (on the outside and from the inside)
- Polypropylene filtering melt-blown non-woven fabric

Additional elements:

- Exhalation valve
- Head band pins for length adjustment
- Head band

You no longer have to waste time trying to adjust the nosepiece to fit your face and your glasses will not fog up. 600-SERIES half masks are equipped with pins for head band length adjustment, which improves facial fit and, as a result, half mask performance. The exhalation valve makes breathing resistance very low.

Filtering half mask			
FS-623V FFP2 NR D			
Certificate UE/1117/2025/1437 Edition 1	Date of issue 12.02.2025	Standard EN 149:2001 + A1:2009	Protection class Class P2 
Certification body: CIOP-PIB 1437 Central Institute for Labour Protection – National Research Institute			
Supervising body: CIOP-PIB 1437* Central Institute for Labour Protection – National Research Institute			

Requirements

The half mask meets the latest requirements:

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC.

Contraindications

The half mask must not be used under low-oxygen conditions (below 17%), which means that it is forbidden to use it in confined spaces, such as canals, manhole shafts, tanks. Also, the half mask does not protect against vapours and gases that are harmful for health and pose a life hazard. Do not use while extinguishing fire. The half mask does not supply oxygen. The half mask will not provide adequate facial fit for people with unshaved or bearded face. The half mask does not protect against aerosols containing radioactive and carcinogenic particles, microorganisms (bacteria, viruses, fungi and their derivatives) or enzymes.

Primary packaging: 50 pcs per plastic bag

Collective packaging: 400 pcs per carton

*This number is on the product after the CE mark